

## Microprocessor Controlled Display Unit in 28 TE Table Housing

**Type PAX-TG**

- Display Freely Scalable
- 5-Digit LED-Display
- Extendable with up to 3 Output Modules
- 20 Measurements/s
- Minimum-Maximum Value Display
- 16-Step Linearity



### DESCRIPTION:

This measuring amplifier is a very flexible and precise laboratory device. Sensor signals can be displayed, scaled and processed.

The device gets easily programmed by 5 keys through the user interface. Additional functions e.g. Min.-Max. memory, tare and delete memory can be carried out.

The measuring amplifier is freely scaled by the 2-point method or by applying input signals. The sensor can be easily calibrated by control keys (presumed that the sensor has 100% calibration control). Up to 16 steps linearization is possible as well.

The decimal point can be selected freely. If necessary, the display can be stabilized by a rounding factor and digital filtration.

A code avoids unintended changes of parameters.

The device can be equipped with various output interfaces. In each case the device can be equipped at the max. with a limit value output, an analog output and an interface plug-in module.

The physical unit is backlit and should be specified when placing the order.

Excel® is either a registered brand or brand of the Microsoft Corporation in the USA and/or other countries.

All trademarks or brands used in this document refer only to the respective product or the holder of the trademark or brand. Lorenz Messtechnik GmbH does not raise claims to other than their own trademarks or brands.

### TECHNICAL DATA:

| Type                      | PAXD<br>0000-TG                                                              | PAXD<br>0010-TG                                              | PAXS<br>0000-TG                    | PAXS<br>0010-TG                                              |
|---------------------------|------------------------------------------------------------------------------|--------------------------------------------------------------|------------------------------------|--------------------------------------------------------------|
| Art. No.                  | 101028                                                                       | 101029                                                       | 100888                             | 101015                                                       |
| Supply                    | 85...250 V AC<br>50/60 Hz<br>15 VA                                           | 11...36 V DC<br>11 W or 24 V<br>AC ±10%<br>50/60 Hz<br>15 VA | 85...250 V AC<br>50/60 Hz<br>15 VA | 11...36 V DC<br>11 W or 24 V<br>AC ±10%<br>50/60 Hz<br>15 VA |
| Measuring Rate<br>Display | 20 Measurements/s<br>5-digit, Height 14 mm, red LED, device freely definable |                                                              |                                    |                                                              |

### Sensor Side

|                             |                                                                           |                                     |
|-----------------------------|---------------------------------------------------------------------------|-------------------------------------|
| Excitation                  | 24 V DC 50 mA                                                             | 10 V DC 125 mA (5 V 65 mA)          |
| Temp. Coefficient           | 40 ppm/°C                                                                 | 20 ppm/°C                           |
| Signal Input /<br>Impedance | ±2 V / 1.066 MΩ<br>±20 V / 1.066 MΩ<br>±20 mA / 11.1 Ω<br>±200 mA / 1.1 Ω | ±24 mV / 100 MΩ<br>±240 mV / 100 MΩ |

### Miscellaneous

|                           |                    |
|---------------------------|--------------------|
| Service Temperature Range | 0...+45 °C         |
| Storage Temperature Range | -40...+85 °C       |
| Dim. (W x H x D)          | 187 x 148 x 263 mm |
| Weight                    | approx. 2.6 kg     |
| Level of Protection       | IP 21              |

| Options | Art. No.   | Function                                                            |
|---------|------------|---------------------------------------------------------------------|
| DC10E   | 101016     | Interface module RS485                                              |
| DC20E   | 100949     | Interface module RS232                                              |
| DL10E   | 101035     | Analog output 0...10 V or 0...20 V, 4...20 mA                       |
| DS10E   | 100950     | 2 limit value relays, change-over contacts                          |
| DS20E   | 101036     | 4 limit value relays closing contact                                |
| DS30E   | 101037     | 4 limit value transistor outputs NPN                                |
| DS40E   | 101039     | 4 limit value transistor outputs PNP                                |
| EXT     | 101040     | External control: tare, delete buffer...                            |
| LPAX    | On request | Device with 38 mm high LED-display                                  |
| PAX-DP  | 110067     | 2 galvanically separated input channels (by active sensors)         |
| PAX-XLS | 106872     | Measurement Software for Excel®, applicable with option RS232, only |

For further specifications see data sheet PAX respectively PAX-DP.